


ENVIRO WHEEL WASH

A HISTORY OF INNOVATION



MIN 1 WEEK HIRE

STANDARD SPECIFICATIONS:

Product Code	300002
Unit Name	Enviro Wheel Wash
Dimensions with ramps	62 x 24ft / 20 x 7.3m
Dimensions without ramps	22 x 24ft / 6.7 x 7.3m
Weight	8500Kg
Weight (with pump)	17000Kç
Power type	6" Diesel water pump
Steel fabricated wash area	~
Internal removable rumble road s	ections 🗸
25mm water inlet	
(c/w ball cock fitted)	~
Heavy duty lifting/lashing points	<u> </u>
Automated magic eye system	<u> </u>
Dig Measurements	6.3m length x 1.02n depth x 3.5m widtl

Our enviro wheel wash is the ideal solution for demolition, quarrying and ground works sites where trucks, dumpers and lorries are regularly passing through heavy duty mud, dirt and debris.

Our fully automated and totally self-sufficient enviro wheel wash is perfect for sites where sticky clay and mud can be a big problem. As vehicles pass through the wheel wash, exceptionally powerful jets spray water onto the wheels, chassis and undersides, cleaning the vehicles without them even needing to stop. The wheel wash is environmentally friendly and utilises the latest water filtration technology combined with a 100 percent water recirculation system. It doesn't require an operative and is easy to maintain due to an innovative easy-clean water catchment area. Furthermore, it requires no electricity power source because it runs off a simple yet reliable 6" diesel pump.

The enviro wheel wash can be elevated and placed directly onto a surfaced area with ramps or excavated into the ground making it suitable for a large variety of sites.

KEY FEATURES:

- Powered heavy duty wheel wash
- Steel fabricated wash area
- Heavy duty lifting and lashing points
- Cleaning area with vertical spray jets
- Automatic sensors

OPTIONAL EXTRAS AVAILABLE

- Electric pumps
- Water fills
- Water Tank / Bowser
- Header Tank / Bowser



















